



## 550 XP®

Husqvarna 550 XP® is developed for tree care professionals and skilled land owners. The saw has a ground breaking design and is loaded with innovative solutions for efficient, convenient operation. Our unique X-Torq® engine technology provide more power where you need it, up to 20% less fuel consumption and 75% less exhaust emission.



### X-TORQ®

Deliver lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.



### AUTOTUNE

AutoTune gives optimal engine performance throughout automatic engine setting. No time spent on carburettor adjustments. It compensates for different fuels, altitude, humidity, temperature and clogged air filter.



### AIR INJECTION

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.



### LOWVIB®

Effective anti-vibration dampeners absorb vibration, sparing the user's arms and hands.

## Features

- Adjustable chain oil pump
- Quick-release air filter
- Intuitive, combined choke/stop control
- Quick and easy chain adjustment
- Magnesium crankcase designed for professional use
- Easy to maintain with snap locked filter cover
- Easy to maintain with snap locked cylinder cover
- Maximum durability for tough applications
- Smart Start® for easy starting
- Easy and convenient to handle in any situation.
- Felling marks for correct felling direction
- Fuel level window
- Fuel pump for easy starting
- The retaining function prevents losing the bar nuts.
- Increased safety, inertia activated chain brake

## Technical data

Cylinder displacement	50.1 cm <sup>3</sup> / 3.06 cu.inch
Power output	2.8 kW
Maximum power speed	10200 rpm
Fuel tank volume	0.52 lit / 17.58 fl oz
Fuel consumption	446 g/kWh
Idling speed	2800 rpm
Spark plug	NGK CMR6H
Electrode gap	0.5 mm / 0.02 "
Torque, max.	2.8 Nm/6900 rpm
Oil tank volume	0.27 lit / 0.57 US pint
Oil pump type	Automatic
Equivalent vibration level (ahv, eq) front / rear handle	2.8/3.7 m/s <sup>2</sup>
Sound pressure level at operators ear	106 dB(A)
Sound power level, guaranteed (LWA)	116 dB(A)
Chain pitch	.325"
Recommended bar length, min-max	33-50 cm / 13"-20"
Chain speed at max power	19.6 m/s / 64.3 fts
Chain gauge	0.05 "
Weight (excl. cutting equipment)	4.9 kg / 10.8 lbs

### ARTICLES

966 64 81-15	15" - .325" - H25 - CE- All ex US50, CAN	€ 699.18	€ 769.99
--------------	--	----------	----------

