

High-performance and robust

## The K 2000 series

- Single-part Roto-Mold-chassis and therefore extremely stable and robust
- Integrated trolley takes steps and rough ground in its stride
- Integrated hose drum with foldable crank (TS T)
- 5 m power lead with cable reel
- Dirtkiller lance with stainless steel pipe, Vario-Jet lance lance with stainless steel pipe with fully adjustable spray angle from pencil to wide fan as well as high and low pressure
- Storage for trigger gun with safety catch and lances
- Total-Stop system
- Low pressure detergent



K 2000 TST with hose drum



K 2000 TS  
without hose drum



Technical specifications	K 2160 TS T	K 2195 TS T	K 2175 TS T	K 2160 TS	K 2195 TS	K 2175 TS
Ord. no.	41,781 1	41,785 1	41,783 1	41,780 1	41,784 1	41,782 1
Operating pressure, continuously adjustable	30-140 bar / 3-14 MPa	30-180 bar / 3-18 MPa	30-160 bar / 3-16 MPa	30-140 bar / 3-14 MPa	30-180 bar / 3-18 MPa	30-160 bar / 3-16 MPa
Max. admissible overpressure	160 bar / 16 MPa	195 bar / 19,5 MPa	175 bar / 17,5 MPa	160 bar / 16 MPa	195 bar / 19,5 MPa	175 bar / 17,5 MPa
Water output	11 l/min (660 l/h)	8 l/min (480 l/h)	12 l/min (720 l/h)	11 l/min (660 l/h)	8 l/min (480 l/h)	12 l/min (720 l/h)
Motor speed	1,400 rpm	1,400 rpm	1,400 rpm	1,400 rpm	1,400 rpm	1,400 rpm
Connected load	230 V, 14 A, 50 Hz	230 V, 14 A, 50 Hz	400 V, 6,7 A, 50 Hz	230 V, 14 A, 50 Hz	230 V, 14 A, 50 Hz	400 V, 6,7 A, 50 Hz
Power intake / Power output	3,2 kW / 2,4 kW	3,2 kW / 2,4 kW	3,3 kW / 2,6 kW	3,2 kW / 2,4 kW	3,2 kW / 2,4 kW	3,3 kW / 2,6 kW
Weight	39,5 kg	39,5 kg	39,5 kg	37 kg	37 kg	37 kg
Features & Equipment	Ord. no.	Ord. no.	Ord. no.	Ord. no.	Ord. no.	Ord. no.
Steel braided high-pressure hose, NW 6	15 m (48,015)	15 m (48,015)	15 m (48,015)	10 m (43,416)	10 m (43,416)	10 m (43,416)
Tigger gun with safety catch M2000	(12,480)	(12,480)	(12,480)	(12,480)	(12,480)	(12,480)
Dirtkiller lance with stainless steel pipe	(41,570-042)	(41,570-03)	(41,570-042)	(41,570-042)	(41,570-03)	(41,570-042)
Vario-Jet lance with stainless steel pipe	(41,156 8-042)	(41,156 8-03)	(41,156 8-042)	(41,156 8-042)	(41,156 8-03)	(41,156 8-042)